

10-31-JO

BAKER BOTTS L.L.P.

30 ROCKEFELLER PLAZA
44TH FLOOR
NEW YORK, NEW YORK
10112-4498
212 705 5000
FAX 212 705 5020

AUSTIN
BAKU
DALLAS
HOUSTON
LONDON
MOSCOW
NEW YORK
WASHINGTON

Appln. Trans.
PATENT

**UTILITY PATENT
APPLICATION
TRANSMITTAL**

*(Only for new nonprovisional
applications under 37 CFR 1.53(b))*

Attorney Docket No. A33685

First Named Inventor Jae-Hong Park

Express Mail Label No. EK838861113US

Total Pages 67

JC931 U.S. PTO
09/699618
10/30/00

October 30, 2000

BY EXPRESS MAIL - Label No. EK839861113US

Assistant Commissioner for Patents
Box Patent Application
Washington, DC 20231

Sir:

Enclosed herewith for filing is a patent application of Jae-Hong Park, Woon-Hee Hwang and Jeong-Hwa Ye
entitled METHOD FOR INTERFACING ASYNCHRONOUS MOBILE COMMUNICATION SYSTEM WITH AT
LEAST ONE CORE NETWORK

which includes:

<input checked="" type="checkbox"/> Specification	<u>37</u> Total Pages
<input checked="" type="checkbox"/> Claims	<u>17</u> Total Pages
<input checked="" type="checkbox"/> Abstract	<u>1</u> Total Pages
<input checked="" type="checkbox"/> Drawing(s)	<u>18</u> Total Sheets
<input checked="" type="checkbox"/> formal	
<input type="checkbox"/> informal	

☒ Combined Declaration and Power of Attorney 4 Total Pages

☒ Newly executed (original or copy)

☐ Copy from a prior application

(for continuation/divisional only - **must be filed to avoid surcharge for late filing**)

If a continuing application, check appropriate box:

☐ Continuation ☐ Divisional ☐ Continuation-In-Part (CIP)
of prior application No.

☐ Amend the specification by inserting, before the first line, the following sentence:

"This is a ☐ continuation ☐ divisional ☐ continuation-in-part
of copending application Serial No. filed ."

Attorney Docket No. A33685

- ☒ An Assignment of the invention to Hyundai Electronics Industries Co., Ltd.
☒ is attached. A separate cover sheet in compliance with 37 CFR 3.28 and 3.31 is included.
☐ will follow.
☐ has been filed in the prior application

- ☐ Small Entity Statement(s) **ENCLOSED**.
☐ Small Entity Statement filed in prior application. Status still proper and desired.

- ☐ Information Disclosure Statement (IDS) PTO-1449
☐ Copies of IDS Citations.

☐ Preliminary Amendment

☒ Return Receipt Postcard

☐ Other _

☐ Cancel in this application original claims _ of the prior application before calculating the filing fee.

The filing fee has been calculated as shown below:

FOR	(Col. 1) No. Filed	(Col. 2) No. Extra	Small Entity Rate	Fee	OR	Other Than A Small Entity Rate	Fee
Basic Fee							\$710.00
Total Claims	29	-20 = 9	x 9 =	\$0.00	x 18 =		\$162.00
Ind. Claims	3	-3 = 0	x 40 =	\$0.00	x 80 =		\$0.00
Multiple Dependent Claim			+ 135 =		+ 270 =		
			Total	<u>\$0.00</u>			<u>\$872.00</u>

* If the difference in Col. 1 is less than zero, enter "0" in Col. 2.

Fee Payment Being Made:

☒ Enclosed

☒ Basic filing fee \$872.00

☒ Recording Assignment \$40.00
 [\$40.00; 37 CFR 1.21(h)]

Total Fees Enclosed \$912.00

☒ A check in the amount of \$872 & 40 to cover filing fee and assignment recordation fee is enclosed.

Appln. Trans.
PATENT

Attorney Docket No. A33685

Priority

[x] Priority of application Country Korea, Appln. No. 1999-46999 filed October 28, 1999 and 1999-51355 filed November 18, 1999 is claimed under 35 U.S.C. 119.

[x] Certified Copy of Priority Document(s) Country Korea, Appln. No. 1999-46999 filed October 28, 1999 and 1999-51355 filed November 18, 1999.

[x] is/are attached [] will follow [] has been filed in the parent application S/N .

[X] The Commissioner is hereby authorized to charge payment of any additional filing fees required under 37 CFR 1.16, 1.17, and 1.21(h) associated with this communication or credit any overpayment to Deposit Account No. 02-4377. Two copies of this sheet are enclosed.

AKER BOTTS L.L.P.

By

Ronald B. Hildreth

PTO Registration No. 19,498

Enclosures

METHOD FOR INTERFACING ASYNCHRONOUS MOBILE
COMMUNICATION SYSTEM WITH AT LEAST ONE CORE NETWORK

Field of the Invention

5

The present invention relates in general to a method for interfacing an asynchronous mobile communication system with a least a core network; and, more particularly to a method for interfacing an asynchronous mobile communication system with a plurality of core networks each having a different operating type.

Description of the Prior Art

15

In a conventional synchronous mobile telecommunication system, a synchronous mobile station is connected to a synchronous radio network (for example, a CDMA-2000 radio network), which is in turn connected to an ANSI-41 core network.

20

In a conventional asynchronous mobile telecommunications system, an asynchronous mobile station is connected to an asynchronous radio network (for example, a universal mobile telecommunication system (UMTS) terrestrial radio access network (UTRAN)), which is in turn connected to a global system for mobile-communications-mobile application part (GSM-MAP) core network.

25

Fig. 1A is a view showing the core network interface

architecture of the conventional synchronous mobile telecommunications system. In this drawing, the reference numeral 11 denotes a synchronous mobile station, 12 denotes a synchronous radio network (i.e., a code division multiple access-2000 (CDMA-2000) radio network) which performs a data interfacing operation with the synchronous mobile station 11 and includes a synchronous base transceiver station/base station controller (BTS/BSC), and 13 denotes a synchronous core network, called ANSI-41 core network, which is connected to the synchronous radio network 12 and includes several systems such as mobile switching center (MSC) 14.

In the above core network interface architecture of the conventional synchronous mobile telecommunications system, the synchronous mobile station 11 can be connected to only the synchronous radio network 12 as well known to one skilled in the art, which is in turn connected to the synchronous core network 13, thereby allowing the synchronous mobile station 11 to be interfaced with only the synchronous core network 13.

Fig. 1B is a view showing the core network interface architecture of the conventional asynchronous mobile telecommunications system. In this drawing, the reference numeral 21 denotes an asynchronous mobile station, 22 denotes an asynchronous radio network (i.e., a UTRAN) which includes a base transceiver station (BTS) and a radio network controller (RNC), and 23 denotes an asynchronous core network, called GSM-MAP core network, which includes

several systems such as mobile switching center (MSC) 24.

In the above core network interface architecture of the conventional asynchronous mobile telecommunications system, the asynchronous mobile station 21 is connected to the asynchronous radio network 22 (i.e., UTRAN) which is in turn connected to the asynchronous core network 23, thereby allowing the asynchronous mobile station 21 to perform a data interfacing operation with the asynchronous core network 23.

Fig. 2A is a view showing the layered protocol structure of the conventional synchronous mobile telecommunications system. In this drawing, the reference numeral 30 denotes a synchronous mobile station, 40 a synchronous radio network and 50 a synchronous core network connected to the synchronous radio network 40.

The synchronous mobile station 30 includes a layer3 31, a layer2 35 and a layer1 36. The layer3 31 includes a synchronous call control (CC) entity 32 for management of a call and a synchronous mobility management (MM) entity 33 for management of a mobility.

The layer1 36 is a physical layer which offers data transport services to higher layers and transfers transport blocks over a radio interface.

The layer2 35 is a data link layer which includes following sub layers, a medium access control (MAC) sub layer and a radio link control (RLC) sub layer. However, the sub layers are not shown in this drawing.

The MAC sub layer offers data transfer services on logical channels to a higher layer (RLC sub layer) and on transport channels to a lower layer (the physical layer 36). The MAC sub layer is responsible for mapping of the logical channel onto the appropriate transports channel.

The RLC sub layer offers data transfer services on primitive to a higher layer and on logical channels to a lower layer (MAC sub layer). Also, the RLC sub layer performs an error correction, a duplicate detection, a ciphering and a flow control of the data.

The layer3 31 is a network layer which includes following sub layers, a synchronous radio resource (RR) sub layer, a synchronous call control (CC) entity 32 and a mobility management (MM) entity 33. In synchronous system, the synchronous RR sub layer is not apparently separated from the others in the layer3 31.

The RR sub layer offers data transfer services on primitive to a lower layer (RLC sub layer) and handles a control plane signaling of the layer3 31 between a user equipment (UE) and a synchronous radio network. The RR sub layer manages a radio resource. Also, the RR sub layer assigns/re-configures/releases the radio resource to UE/UTRAN.

The CC entity handles a call control signaling of layer3 between the UEs and the synchronous radio network.

The MM entity handles a mobility management signaling of layer3 between the user equipments (UEs) and the synchronous

radio network.

The layers 3 to 1 31, 35 and 36 in the synchronous mobile station 30 communicate with corresponding layers 41, 45 and 46 in the synchronous radio network 40.

5 The synchronous radio network 40 includes a layer3 41, a layer2 45 and a layer1 46. The layers 3 to 1 in the synchronous radio network 40 correspond respectively to those in the synchronous mobile station 30.

10 The layers 3 to 1 41, 45 and 46 in the synchronous radio network 40 communicate with corresponding layers 31, 35, 36, 51, 55 and 56 in the synchronous mobile station and the synchronous core network 50.

15 The synchronous core network 50 includes a layer3 51, a layer2 55 and a layer1 56. The layers 3 to 1 in the synchronous radio network 50 correspond respectively to those in the synchronous mobile station 30.

 The layers 3 to 1 51, 55 and 56 in the synchronous core network 50 communicate with corresponding layers 41, 45 and 46 in the synchronous radio network 40.

20 In the conventional synchronous mobile station and radio network as the layered protocol structure, the synchronous mobile station 30 receives a Sync channel message from the synchronous radio network 40 over a Sync channel and acquires information necessary to its connection to the
25 synchronous core network 50, including information related to the synchronous core network 50 and information about the synchronous radio network 40, from the received Sync channel

message.

In other words, for interfacing with the synchronous ANSI-41 network via the synchronous radio network, the synchronous mobile station acquires system information (i.e.,
5 information related to the radio network and core network) through a system determination sub-state, a pilot channel acquisition sub-state, a Sync channel acquisition sub-state and a timing changing sub-state after it is powered on.

Fig. 2B is a view showing the layered protocol structure
10 of the conventional asynchronous mobile telecommunications system. In this drawing, the reference numeral 60 denotes an asynchronous mobile station, 70 a UTRAN and 80 an asynchronous core network.

The asynchronous mobile station 60 includes a layer3 61,
15 a layer2 65 and a layer1 66. In particular, the layer3 61 includes a non-access stratum (NAS) part and an access stratum (AS) part. The NAS part includes an asynchronous call control (CC) part 62 for management of a call and an asynchronous mobility management (MM) part 63 for management
20 of a mobility. The AS part includes an asynchronous radio resource control (RRC) part. In the asynchronous system, the asynchronous RRC sub layer is apparently separated from the NAS part. Functions of the asynchronous RRC sub layer are the same as those of the synchronous RR sub layer.

25 The UTRAN 70 includes a layer3 71, a layer2 73 and a layer1 74. The layer3 71 of the UTRAN 70 has no NAS part having asynchronous CC part and asynchronous MM part. The

layers 3 to 1 of the UTRAN 70 are connected and correspond respectively to those in the asynchronous mobile station 60 and those in the asynchronous core network 80. However, since the UTRAN 70 does not have the NAS part, i.e., the asynchronous CC part and the asynchronous MM part, the NAS parts of the asynchronous mobile station 60 and the asynchronous core network 80 are coupled to each other not through the UTRAN 70.

The asynchronous core network 80 includes a layer3 having a NAS part 81 connected to that of the asynchronous mobile station 60 and a AS part, a layer2 85 and a layer1 86 connected respectively to those in the UTRAN 70. The NAS part includes an asynchronous CC part 82 for management of a call and an asynchronous MM part 83 for management of a mobility.

Functions of the layer 3 to 1 of the asynchronous system are similar with those of the synchronous system except for an operating type. Therefore, detailed description of the layer 3 to 1 will be skipped.

The more detailed descriptions about layered protocol structures are well taught in 3rd Generation Partnership Project (3GPP), Technical Specification Group (TSG) - Radio Access Network (RAN): 3G TS25.301 (Radio Interface Protocol Architecture), 3G TS25.302 (Services provided by the physical layer), 3G TS25.321 (MAC Protocol Specification), 3G TS25.322 (RLC Protocol Specification) and 3G TS25.331 (RRC Protocol Specification) in detail.

The synchronous mobile station 30 receives a synchronous channel message through a synchronous channel from the synchronous radio network 40, and obtains information necessary for connecting the mobile station to the core network, from the synchronous channel message. The synchronous channel message includes information related to the synchronous radio network and a core network connected thereto.

The asynchronous mobile station 60 receives a system information message through a broadcast channel (BCCH), and obtains information necessary for connecting the mobile station to the core network, from the system information message. The system information message includes information related to the asynchronous radio network and a core network connected thereto.

IMT-2000 systems are the third generation systems which aim to unify the various mobile communication networks and services into one to provide many mobile communication services. The systems can provide multimedia services under multi-environments through various air-interfaces and high capacity. Also, in the aspect of services, the systems can provide multimedia services of speech, image and data up to the rate of 2 Mbps and an international roaming. And, in the aspect of network, the systems are total systems which are based on ATM networks and combine fixed and wireless systems.

IMT-2000 system requires new system concept, high-level adaptation technology, and novel network technology, as well

all conventional technologies which were already adopted in the second digital cellular system.

As described above, in the next-generation mobile telecommunication system such as the IMT-2000 system, either the GSM-MAP network used in the above conventional asynchronous mobile telecommunications system or the ANSI-41 network used in the above conventional synchronous mobile telecommunications system should be employed as a core network in order to perform an international roaming in a synchronous or asynchronous mobile telecommunications system of an IMT-2000 system.

According to network deployment scenarios, the IMT-2000 system can have the following four interface architectures; first: synchronous mobile station - synchronous radio network - synchronous ANSI-41 network, second: synchronous mobile station - synchronous radio network - asynchronous GSM-MAP network, third: asynchronous mobile station - asynchronous radio network - synchronous ANSI-41 network and fourth: asynchronous mobile station - asynchronous radio network - asynchronous GSM-MAP network.

The IMT-2000 system has the four interface architectures as mentioned above. Therefore, the hybrid type synchronous mobile station must recognize an operating type of a core network currently connected thereto, and the hybrid type synchronous radio network should provide core network operating type information and others information to the hybrid type synchronous mobile station. The core network

operating type information and the others information must be contained in the Sync channel message that the synchronous mobile station, after being powered on, receives through the Sync channel in the above-mentioned conventional
5 interfacing manner.

Similarly, the hybrid type asynchronous mobile station must recognize an operating type of a core network currently connected thereto, and the hybrid type asynchronous radio network should provide the core network operating type
10 information and others information to the hybrid type asynchronous mobile station. The core network operating type information and the others information must be contained in the system information message transmitted to the asynchronous mobile station, after being powered on, so that
15 the asynchronous mobile station receives through the broadcast control channel (BCCH) in the above-mentioned conventional interfacing manner.

Fig. 3A is a view showing a synchronous ANSI-41 core network interface architecture of a hybrid type synchronous
20 radio network. In this drawing, the reference numeral 100 denotes a hybrid type synchronous mobile station, 110 a hybrid type synchronous radio network, and 120 a synchronous core network.

Fig. 3B is a view showing an asynchronous GSM-MAP core network interface architecture of the hybrid type
25 synchronous radio network. In this drawing, the reference numeral 100 denotes a hybrid type synchronous mobile

station, 110 a hybrid type synchronous radio network, and 130 an asynchronous core network.

Fig. 3C is a view showing an asynchronous GSM-MAP core network interface architecture of a hybrid type asynchronous radio network. In this drawing, the reference numeral 210 denotes a hybrid type asynchronous mobile station, 220 denotes a hybrid type UTRAN which is a hybrid type asynchronous radio network, and 230 denotes a core network which is connected to the hybrid type UTRAN 220.

Fig. 3D is a view showing a synchronous ANSI-41 core network interface architecture of the hybrid type asynchronous radio network. In this drawing, the reference numeral 210 denotes a hybrid type asynchronous mobile station, 220 denotes a hybrid type UTRAN which is a hybrid type asynchronous radio network, and 240 denotes a core network which is connected to the hybrid type UTRAN 220.

In order to be operable adaptively to the above four interface architectures, each of the hybrid type synchronous and asynchronous mobile stations in the next-generation mobile telecommunications system has both asynchronous CC and MM protocol entities serving for the GSM-MAP core network and synchronous CC and MM protocol entities serving for the ANSI-41 core network at the layer3 in the protocol stack structure, which is a different from each of the conventional synchronous and asynchronous mobile stations.

Fig. 4A is a view showing the layered protocol structure of a hybrid type synchronous mobile station, a

hybrid type synchronous radio network and the synchronous ANSI-41 core network. In this drawing, the reference numeral 100 denotes a hybrid type synchronous mobile station, 110 denotes a hybrid type synchronous radio network, and 120 denotes an ANSI-41 core network which is a synchronous core network connected to the hybrid type synchronous radio network 110.

The hybrid type synchronous mobile station 100 includes a layer3 101, a layer2 107 and a layer1 108. The layer3 101 includes a synchronous CC part 102, a synchronous MM part 103, an asynchronous CC part 104, an asynchronous MM part 105 and a synchronous radio resource part 106. The hybrid type synchronous mobile station 100 selectively makes a CC/MM protocol active according to a core network operating type. Information for identifying the core network operating type is given to the hybrid type synchronous mobile station 100.

For example, if the hybrid type synchronous mobile station 100 is currently connected to the ANSI-41 core network 120, the layer3 101 therein activates protocols of the synchronous CC part 102 and synchronous MM part 103 to perform a message interfacing operation with the ANSI-41 core network 120.

The hybrid type synchronous radio network 110 includes a layer3 111, a layer2 115 and a layer1 116, which activate their protocols corresponding respectively to those in the hybrid type synchronous mobile station 100 and those in the

ANSI-41 core network 120 to transmit and receive messages.

The ANSI-41 core network 120 includes a layer3 121, a layer2 125 and a layer1 126. The layer3 121 includes a synchronous CC part 122, a synchronous MM part 123 and a synchronous RR part 124.

On the other hand, a hybrid type synchronous mobile station, a hybrid type synchronous radio network and an asynchronous core network have layered protocol structures as shown in Fig. 4B when the core network connected thereto is of an asynchronous operating type as shown in Fig. 3B.

In Fig. 4B, the reference numeral 100 denotes a hybrid type synchronous mobile station, 110 denotes a hybrid type synchronous radio network, and 130 denotes a GSM-MAP core network which is an asynchronous core network.

The hybrid type synchronous mobile station 100 includes a layer3 101 having a NAS part and an AS part, a layer2 107 and a layer1 108. The NAS part includes a synchronous CC part 102, a synchronous MM part 103, an asynchronous CC part 104 and an asynchronous MM part 105. The AS part includes a synchronous RR part 106. The hybrid type synchronous mobile station 100 selectively makes a CC/MM protocol active according to a core network operating type.

For example, if the hybrid type synchronous mobile station 100 is currently connected to the GSM-MAP core network 130, the layer3 101 therein activates protocols of the asynchronous CC part 104 and asynchronous MM part 105 to perform a message interfacing operation with the GSM-MAP

core network 130.

The hybrid type synchronous radio network 110 includes a layer3 111 having a NAS part and an AS part, a layer2 115 and a layer1 116, which activate their protocols corresponding respectively to those in the hybrid type synchronous mobile station 100 and those in the GSM-MAP core network 130 to transmit and receive messages.

The GSM-MAP core network 130 includes a layer3 131 having a NAS part and an AS part, a layer2 135 and a layer1 136. The NAS part includes an asynchronous CC part 132 and an asynchronous MM part 133. The AS part includes an asynchronous RRC part 134.

The layers 3 to 1 of the hybrid type synchronous radio network 110 are connected and correspond respectively to those in the hybrid type synchronous mobile station 100 and those in the asynchronous core network 130. However, the NAS parts of the hybrid type asynchronous mobile station 100 and the asynchronous core network 130 are coupled to each other not through the hybrid type synchronous mobile station 110.

Fig. 4C is a view showing layered protocol structures of a hybrid type asynchronous mobile station, a hybrid type synchronous radio network and a synchronous ANSI-41 core network. In this drawing, the reference numeral 210 denotes a hybrid type asynchronous mobile station, 220 denotes a hybrid type UTRAN which is a hybrid type asynchronous radio network, and 230 denotes an ANSI-41 core network connected to the hybrid type UTRAN 220.

The hybrid type asynchronous mobile station 210 includes a layer3 211, a layer2 217 and a layer1 218. The layer1 includes a synchronous CC part 212, a synchronous MM part 213, an asynchronous CC part 214, an asynchronous MM part 215 and asynchronous RRC part 216 and selectively activates a synchronous CC/MM protocol or an asynchronous CC/MM protocol.

For example, if the hybrid type asynchronous mobile station 210 is currently connected to the ANSI-41 core network 230, the layer1 therein activates a protocol between the synchronous CC part 211 and synchronous MM part 212 to perform a message interfacing operation with the ANSI-41 core network 230.

Fig. 4D is a view showing layered protocol structures of a hybrid type asynchronous mobile station, a hybrid type asynchronous radio network and an asynchronous GSM-MAP core network. In this drawing, the reference numeral 210 denotes a hybrid type asynchronous mobile station, 220 denotes hybrid type a UTRAN which is a hybrid type asynchronous radio network, and 240 denotes an asynchronous GSM-MAP core network connected to the hybrid type UTRAN 220.

The hybrid type asynchronous mobile station 210 includes a layer3 211 having a NAS part and an AS part, a layer2 217 and a layer1 218. The NAS part includes a synchronous CC part 212, a synchronous MM part 213, an asynchronous CC part 214 and an asynchronous MM part 215 and selectively activates a synchronous CC/MM protocol or an

asynchronous CC/MM protocol. The AS part includes an asynchronous RRC part 216.

The hybrid type synchronous radio network 210 includes a layer3 211 having a NAS part and an AS part, a layer2 225 and a layer1 226, which activate their protocols corresponding respectively to those in the hybrid type synchronous mobile station 210 and those in the GSM-MAP core network 240 to transmit and receive messages.

The GSM-MAP core network 240 includes a layer3 241 having a NAS part and an AS part, a layer2 245 and a layer1 246. The NAS part includes an asynchronous CC part 242 and an asynchronous MM part 243. The AS part includes an asynchronous RRC part 244.

For example, if the hybrid type asynchronous mobile station 210 is currently connected to the GSM-MAP core network 240, the NAS part therein activates protocols of the asynchronous CC part 214 and asynchronous MM part 215 to perform a message interfacing operation with the GSM-MAP core network 240.

The layers 3 to 1 of the hybrid type synchronous radio network 220 are connected and correspond respectively to those in the hybrid type synchronous mobile station 210 and those in the asynchronous core network 240. However, the NAS parts of the hybrid type asynchronous mobile station 210 and the asynchronous core network 240 are coupled to each other not through the hybrid type asynchronous mobile station 220.

A communication protocol between a synchronous mobile

station and a synchronous mobile network is referred to an Air-interface protocol. For example, an Interim Standard (IS)-2000 protocol is used as the Air-interface protocol.

A communication protocol between a synchronous mobile network and a synchronous core network, for example, an ANSI-41 network is referred to an A-interface protocol. For example, a third generation interoperability specification (3G-IOS) is used as the A-interface protocol.

The IMT-2000 system has the four interface architectures as mentioned above. Therefore, the synchronous mobile station must recognize an operating type of a core network currently connected thereto, and the synchronous radio network should provide core network operating type information and others information to the synchronous mobile station. The core network operating type information and the others information must be contained in the Sync channel message that the synchronous mobile station, after being powered on, receives through the Sync channel in the above-mentioned conventional interfacing manner.

Similarly, the hybrid type asynchronous mobile station must recognize an operating type of a core network currently connected thereto, and the asynchronous radio network should provide the core network operating type information and others information to the asynchronous mobile station. The core network operating type information and the others information must be contained in the system information message transmitted to the asynchronous mobile station,

after being powered on, so that the asynchronous mobile station receives through the broadcast control channel (BCCH) in the above-mentioned conventional interfacing manner.

5 The asynchronous radio network can recognize the operating type of the core network by communicating a message with the core network or by a hardware device including a dip switch. The asynchronous radio network inserts the core network type information into a
10 predetermined location of a system information message and transmits the system information message to the asynchronous mobile station, so that the asynchronous mobile station operates a call control (CC) entity and a mobility management (MM) entity based on the core network type
15 information. For example, the predetermined location is a master information block in which information for a control and a scheduling of a system information block is written. The master information block is necessarily included in the system information message.

20 However, the asynchronous mobile station can be coupled to two or more core networks each having a different operating type. For example, both of the asynchronous GSM-MAP core network and the synchronous ANSI-41 core network can be coupled to the asynchronous mobile communication
25 system.

 When the mobile communication system is coupled to two core networks each having a different operating type, the

asynchronous radio network should transmit both kinds of the core network type information to the asynchronous mobile station. In order to communicating between the asynchronous mobile communication system and the core network, one core network should be selected by the asynchronous mobile communication system. In other words, one of the asynchronous radio network or the asynchronous mobile station should select one of the core networks. At this time, it is more efficient that the mobile station selects, because the asynchronous radio network does not know capabilities of the asynchronous mobile station.

It is more efficient that the core network is selected by the asynchronous mobile station based on coverage and kinds of services provided by the mobile station and radio environments between the mobile station and the radio network.

one of the core networks. The reason to communicate therewith based on the received core network type information the asynchronous mobile station should select one core network to communicate therewith based on the received core network type information.

However, in the prior art, there is no method for selecting a core network, at the asynchronous mobile station, when a plurality of core networks each having a different operating type are coupled to the asynchronous mobile station. Accordingly, there is a problem in that the asynchronous mobile station cannot be interfaced with the

core network.

Summary of the Invention

5 Therefore, the present invention has been made in view of the above problems, and it is an object of the present invention to provide a method for interfacing an asynchronous mobile communication system and a core network, wherein the asynchronous mobile communication system is coupled to at least two core networks each having a different operating type.

10 In accordance with one aspect of the present invention, there is provided a method for a method for transmitting a message between a mobile communication system and at least a core network, the mobile communication system having a mobile station and a radio network, the method comprising the steps of: a) at the radio network, discriminating an operating type of a core network(s) coupled thereto; b) at the radio network, generating and transmitting a system information message having core network operating type information and information related to the core network; c) if two or more core networks are coupled to the asynchronous mobile communication system, at the mobile station, selecting one core network to be communicated with, based on the system information message; d) operating a call control entity and a mobility management entity according to an operating type of the selected core network; and e) communicating messages between the mobile station and the radio network, the message having a different

15

20

25

data format according to the operating type of the selected core network.

Brief Description of the Drawings

5

The above and other objects, features and advantages of the present invention will be more clearly understood from the following detailed description taken in conjunction with the accompanying drawings, in which:

10 Fig. 1A is a view showing a core network interface architecture of the conventional synchronous mobile telecommunications system; and

15 Fig. 1B is a view showing a core network interface architecture of the conventional asynchronous mobile telecommunications system;

Fig. 2A is a view showing a layered protocol structure of the conventional synchronous mobile telecommunications system;

20 Fig. 2B is a view showing a layered protocol structure of the conventional asynchronous mobile telecommunications system;

Fig. 3A is a view showing a synchronous ANSI-41 core network interface architecture of hybrid type synchronous mobile station and radio network;

25 Fig. 3B is a view showing an asynchronous GSM-MAP core network interface architecture of hybrid type synchronous mobile station and radio network;

Fig. 3C is a view showing an asynchronous GSM-MAP core network interface architecture of hybrid type asynchronous mobile station and radio network;

Fig. 3D is a view showing a synchronous ANSI-41 core network interface architecture of hybrid type asynchronous mobile station and radio network;

Fig. 4A is a view showing layered protocol structures of hybrid type synchronous mobile station and radio network and the synchronous ANSI-41 core network;

Fig. 4B is a view showing layered protocol structures of hybrid type synchronous mobile station and radio network and the asynchronous GSM-MAP core network;

Fig. 4C is a view showing layered protocol structures of hybrid type asynchronous mobile station and radio network and the synchronous ANSI-41 core network;

Fig. 4D is a view showing layered protocol structures of hybrid type asynchronous mobile station and radio network and the asynchronous GSM-MAP core network;

Fig. 5 is a view showing an interface architecture of an asynchronous mobile station, an asynchronous radio network and two core networks each having a different operating type;

Fig. 6 is a view showing data structure of a master information block included in a system information message;

Figs. 7A and 7B are flow charts illustrating a method for interfacing a message at an asynchronous radio network in accordance with the present invention;

Figs. 8A and 8B are flow charts illustrating a method for interfacing a message at an asynchronous mobile station in accordance with an embodiment of the present invention; and

5 Figs. 9A to 9C are flow charts illustrating a method for interfacing a message at an synchronous mobile station in accordance with another embodiment of the present invention.

Detailed Description of the Preferred Embodiments

10 Hereinafter, the preferred embodiments of the present invention will be described in detail with reference to the accompanying drawings.

15 Fig. 5 is a view showing an interface architecture of an asynchronous mobile station, an asynchronous radio network and two core networks each having a different operating type.

20 Reference numerals 210, 220, 230 and 240 denote an asynchronous mobile station, an asynchronous radio network, an asynchronous core network and a synchronous core network, respectively.

25 In order to adaptively set a protocol based on an operating type of the core network 230 or 240 connected thereto, the asynchronous radio network 220 should discriminate an operating type of a core network connected thereto and transmit core network operating type information and information relating to the core network to the

asynchronous mobile station 210. Also, the asynchronous radio network 220 converts a data format of a message received from the asynchronous mobile station 210 based on the operating type of the selected core network, and
5 transmits the converted message to the selected core network.

The asynchronous mobile station obtains information related to the core network from a master information block of a system information message broadcasted through a broadcast channel (BCCH) from the asynchronous radio
10 network. The master information block is illustrated in Fig. 6.

Fig. 6 is a view showing data structure of a master information block included in a system information message.

The master information block of the system information message includes information elements related to a core network, in detail, a core network (CN) type information element, a public land mobile network (PLMN) identity element, a protocol revision (P_REV) element, a minimum
15 protocol revision (MIN_P_REV) element, a system identity element (SID) and a network identity element (NID).

These information elements mentioned above are important for the asynchronous mobile station. Accordingly, the information elements are included in the master information
20 block of the system information message periodically broadcasted.

The CN type information element represents the operating

type of the core network connected to the asynchronous mobile communication system. The CN type information element includes CN operating type information representing the operating type of the core network. In case that the core network is the GSM-MAP core network, the CN operating type information is set as "0" in this specification. In case of the ANSI-41 core network, the CN operating type information is set as "1". In case that both of the GSM-MAP and the ANSI-41 core network are coupled to the mobile communication system, the CN operating type information is set as "0 & 1".

The PLMN identity, which is related to the GSM-MAP core network, means an identity representing networks for the IMT-2000 system. The PLMN identity includes a mobile country code (MCC) indicating a nature or an area to which the asynchronous mobile station belongs, and a mobile network code indicating a network to which the asynchronous mobile station belongs.

The P_REV, the MIN_P_REV, the NID and the SID elements are related to the ANSI-41 core network.

The protocol revision element P_REV means a protocol revision of a call control (CC) and a mobility management (MM) entities of the ANSI-41 core network. The minimum protocol revision element MIN_P_REV means a minimum protocol revision of the CC and the MM entities admitted.

The asynchronous mobile station receives the P_REV, the MIN_P_REV, the NID and the SID from the master information block of the system information message, and compares the

MIN_P_REV with a mobile protocol revision (MOB_P_REV) stored on a memory or a user subscriber identity module. The asynchronous mobile station, based on the comparison result, determines whether the ANSI-41 core network can be selected.

5 Here, the MOB_P_REV means a protocol revision of a CC entity and a MM entity in the asynchronous mobile station.

10 If the CN operating type information indicates the asynchronous GSM-MAP and synchronous ANSI-41 core network, the asynchronous mobile station selects one core network based on a core network selection algorithm stored on the mobile station. The core network selection algorithm selects one core network according to a charging system, a capability of the mobile station, a capability of the asynchronous mobile communication system selected by the mobile station and environments of the asynchronous radio network. The core network selection algorithm is stored in a memory or a user subscriber identity module of the mobile station.

20 For example, if the capability of the mobile station is used for selecting the core network, a number of transmission channels provided by the mobile station, a transmission power of the mobile station, kinds of systems supported by the mobile station, an occupied frequency band and kinds of services are considered.

25 The selection of the core network should be performed before setting a RRC connection, the information related to the selected core network should be transmitted to the

asynchronous radio network. For interfacing the mobile station with the radio network, the RRC connection should be performed. The RRC connection setting means that the mobile station communicates messages with the radio station based on the operating type of the selected core network.

Figs. 7A and 7B are flow charts illustrating a method for interfacing a message at an asynchronous radio network in accordance with the present invention.

An asynchronous radio network 220 detects an operating type of a core network connected thereto at step S111. In other words, the asynchronous radio network 220 obtains a CN operating type information indicating that the core network connected thereto is an asynchronous core network or a synchronous core network.

In order to obtain the operating type of the core network, a hardware device or a management/maintenance message is used. In other words, the asynchronous radio network discriminates the operating type of the core network based on information stored on a dip switch or a read only memory (ROM) at a system install, or based on information in the management/maintenance message received from the core network. Also, both of two methods can be used for obtaining the operating type of the core network.

At step S112, it is determined whether the core network is a GSM-MAP core network or an ANSI-41 core network.

If the core network is a GSM-MAP, a system information message defined in the present 3GPP specification is

transmitted to the asynchronous mobile station 210 at step S113.

In the system information message of this specification, if the core network is the GSM-MAP core network, the CN operating type information is written as "0" and the CN operating type information and information related to the core network are inserted. In other words, if the core network connected the asynchronous radio network is the GSM-MAP core network, the CN operating type information in a core network (CN) information elements field is set as "0", a public land mobile network (PLMN) identity, a core network (CN) domain identity and non-access stratum (NAS) system information are written in the information related to the core network. An information element category field and an UTRAN mobility information elements field are also written the information related to the core network.

The asynchronous radio network communicates a message having a data format defined in the 3GPP specification with the asynchronous mobile station at step S114.

On the contrary, if the core network is not the GSM-MAP core network, it is determined whether the core network is the ANSI-41 core network at step S115. If the core network is the ANSI-41 core network, a new system information message is generated and transmitted to the asynchronous mobile station at step S116. The new system information message includes new information elements related to the ANSI-41 core network. In the new system information message,

the CN operating type information is set as "1", a protocol revision level (P_REV), a minimum protocol revision level (MIN_P_REV), a system identification (SID) and a network identification (NID) are written as the information related to the core network.

An information element category field and an UTRAN mobility information elements field, which are the same as those in the conventional system information message, are also written the information related to the core network.

At step S117, messages having new information elements related to the synchronous ANSI-41 core network are communicated between the asynchronous mobile station and the asynchronous radio network.

If the core network is not the ANSI-41 core network, at determination result of the step S115, it is determined that a plurality of core networks each having a different operating type are coupled to the asynchronous radio network. In this specification, it is assumed that the synchronous ANSI-41 core network and the asynchronous GSM-MAP core network. A new system information message defined in the 3GPP specification is transmitted to the asynchronous mobile station.

In the new system information message, the CN operating type information is written as "0 & 1", and the CN operating type information and information related to the core networks are inserted.

It is determined whether a message is received from the

asynchronous mobile station at step S119. In the received message, information related to a core network selected by the asynchronous mobile station is included.

After receiving the message, at step S120, the asynchronous radio network determines whether the selected core network is a GSM-MAP core network or an ANSI-41 core network. If the selected core network is the GSM-MAP core network, the asynchronous radio network communicates a message having a data format defined in the 3GPP specification with the asynchronous mobile station at step S121. After this time, the asynchronous radio network is interfaced with the GSM-MAP core network.

If the selected core network is not the GSM-MAP core network, at step S122, it is determined whether the selected core network is the ANSI-41 core network.

If the selected core network is the ANSI-41 core network, a new system information message having new information elements related to the ANSI-41 core network is generated and transmitted to the asynchronous mobile station at step S123. After this time, the asynchronous radio network is interfaced with the ANSI-41 core network.

If the selected core network is neither the GSM-MAP core network nor the ANSI-41 core network, the process continues to the step S116 to transmit the system information message to the asynchronous mobile station.

After receiving the system information message having the CN operating type information, the asynchronous mobile

station selects one core network to be interfaced with based on the CN operating type information, and informs the asynchronous radio network of a selection result, which processes is illustrated in Figs. 8A and 8B.

5 Figs. 8A and 8B are flow charts illustrating a method for interfacing a message at an asynchronous mobile station in accordance with the present invention.

10 First, the asynchronous mobile station selects an asynchronous mobile communication system and receives the system information from the asynchronous radio network at steps S211 and S212. The asynchronous mobile station extracts the CN operating type information placed at a predetermined location of the system information message at step S213.

15 It is determined whether the CN operating type information indicates the asynchronous GSM-MAP core network at step S214. If the CN operating type information indicates the asynchronous GSM-MAP core network, the asynchronous mobile station operates asynchronous call control (CC) and mobility management (MM) entities and communicates a message having a data format defined in the 3GPP specification with the asynchronous radio network at steps S215 and 216.

20 If the CN operating type information dose not indicate the asynchronous GSM-MAP core network, it is determined whether the CN operating type information indicates the ANSI-41 core network at step S217.

If the CN operating type information indicates the

synchronous ANSI-41 core network, the asynchronous mobile station operates synchronous call control (CC) and mobility management (MM) entities and communicates a new message having new information elements related to the ANSI-41 core network with the asynchronous radio network at steps S218 and 219.

If the CN operating type information indicates the asynchronous GSM-MAP and synchronous ANSI-41 core network, the asynchronous mobile station selects one core network based on a core network selection algorithm which determines according to a charging system, a capability of the mobile station, a capability of the asynchronous mobile communication system selected by the mobile station and environments of the asynchronous radio network.

For example, if the capability of the mobile station is used for selecting the core network, a number of transmission channels provided by the mobile station, a transmission power of the mobile station, kinds of systems supported by the mobile station, an occupied frequency band and kinds of services are considered.

If the selected core network is the GSM-MAP core network, the asynchronous mobile station operates asynchronous CC and MM entities at step S222. Then, the asynchronous mobile station transmits information related to the selected core network to the asynchronous radio network through the message having the data format defined in the 3GPP specification at step S223. There are some ways that

the information related to the selected core network is transmitted to the asynchronous radio network. For example, there are a random access method, a method using conventional RRC messages and a method using new RRC messages newly defined.

Then, the asynchronous mobile station communicates messages having a data format defined in the 3GPP specification with the asynchronous radio network, with the asynchronous radio network at step 224.

If the selected core network is the ANSI-41 core network, the asynchronous mobile station operates synchronous CC and MM entities at step S226. Then, the asynchronous mobile station transmits information related to the selected core network through a new message having new information elements related to the ANSI-41 core network, and communicates messages having the new information elements at steps S227 and 228.

If the core network is neither the GSM-MAP core network nor the ANSI-41 core network, the process goes back to the step S212 to receive the system information.

In case that a plurality of core networks can be coupled to the asynchronous mobile communication system, the asynchronous radio network is interfaced with the core network selected by the asynchronous mobile station.

Therefore, a subscriber to the asynchronous mobile communication system can use a service provided in the synchronous ANSI-41 core network.

Figs. 9A to 9C are flow charts illustrating a method for interfacing a message at an synchronous mobile station in accordance with another embodiment of the present invention.

The asynchronous mobile station selects an asynchronous mobile communication system and receives the system information from the asynchronous radio network at steps S311 and S312. The asynchronous mobile station extracts the CN operating type information placed at a predetermined location of the system information message at step S313.

It is determined whether the CN operating type information indicates the asynchronous GSM-MAP core network at step S314. If the CN operating type information indicates the asynchronous GSM-MAP core network, the asynchronous mobile station operates asynchronous call control (CC) and mobility management (MM) entities and communicates a message having a data format defined in the 3GPP specification with the asynchronous radio network at steps S315 and 316.

If the CN operating type information dose not indicate the asynchronous GSM-MAP core network, it is determined whether the CN operating type information indicates the ANSI-41 core network at step S317.

If the CN operating type information indicates the synchronous ANSI-41 core network, the asynchronous mobile station operates synchronous call control (CC) and mobility management (MM) entities and communicates a new message having new information elements related to the ANSI-41 core network with the asynchronous radio network at steps S318

and 319.

If the CN operating type information indicates the asynchronous GSM-MAP and synchronous ANSI-41 core network, the asynchronous mobile station extracts the PLMN_ID, the P_REV,
5 MIN_P_REV, the NID and the SID from the master information block of the system information message at step S321.

At step s322, it is determined whether the extracted PLMN_ID is the same as that of the asynchronous mobile station and the MOB_P_REV of the asynchronous mobile station is larger
10 than the extracted MIN_P_REV. If so, the asynchronous mobile station selects one core network according to a core network selection algorithm at step S323. Then, it is determined that the selected core network is GSM-MAP core network at step S324. The asynchronous mobile station operates asynchronous CC and
15 MM entities at step S325.

The asynchronous mobile station informs the asynchronous radio network that the GSM-MAP core network is selected at step S326. Then, at step S327, the asynchronous mobile station communicates messages with asynchronous radio network, the
20 message having a data format defined in the 3GPP specification.

If the selected core network is not the GSM-MAP core network, the asynchronous mobile station operates asynchronous CC and MM entities at step S328. At step S329, the asynchronous mobile station informs the asynchronous radio
25 network that the ANSI-41 core network is selected.

Then, at step S330, the asynchronous mobile station communicates new messages with asynchronous radio network, the

new message having information elements related to the ANSI-41 core network.

At step S340, it is determined whether the extracted PLMN_ID is equal to the PLMN_ID of the mobile station and the
5 extracted MIN_P_REV is larger than the MOB_P_REV of the mobile station. If so, the mobile station selects the GSM-MAP core network and operate asynchronous CC and MM entities at step S341.

10 The asynchronous mobile station informs the asynchronous radio network that the GSM-MAP core network is selected at step S342. Then, the asynchronous mobile station communicates message having data format defined in 3gpp spec with the asynchronous radio network at step S343.

At step S344, it is determined whether the obtained
15 PLMN_ID is not equal to the PLMN_ID of the asynchronous mobile station and the obtained MIN_P_REV is equal to or smaller than the MOB_P_REV of the asynchronous mobile station. If so, the asynchronous mobile station selects the ANSI-41 core network and operate the synchronous CC and MM entities at step S345.

20 The asynchronous mobile station informs the asynchronous radio network that the ANSI-41 core network is selected, and communicates new messages having information elements related to the ANSI-41 core network with the asynchronous radio network at steps S346 and S347.

25 Although the preferred embodiments of the invention have been disclosed for illustrative purpose, those skilled in the art will be appreciate that various modifications, additions

and substitutions are possible, without departing from the scope and spirit of the invention as disclosed in the accompanying claims.

What is claimed is:

1. A method for transmitting a message between an asynchronous mobile communication system and at least a core network, the mobile communication system having a mobile station and a radio network, the method comprising the steps of:

a) at the radio network, discriminating an operating type of a core network(s) coupled thereto;

b) at the radio network, generating and transmitting a system information message having core network operating type information and information related to the core network;

c) at the mobile station, discriminating the operating type of the core network(s) based on the system information message;

d) if one core network is coupled to the asynchronous mobile communication system, operating a call control entity and a mobility management entity according to the operating type of the core network;

e) if two or more core networks are coupled to the asynchronous mobile communication system, at the mobile station, selecting one core network to be communicated with, based on the system information message;

f) operating a call control entity and a mobility management entity according to an operating type of the selected core network;

g) informing the radio network of information related to

the selected core network; and

h) communicating messages between the mobile station and the radio network, the message having a different data format according to the operating type of the core network.

5

2. The method as recited in claim 1, wherein the step a) includes:

a1) receiving core network operating type information; and

10

a2) determining whether the core network connected to the asynchronous mobile communication system is a synchronous core network, asynchronous core network or both of the synchronous and the asynchronous core networks, based on the operating type of the core network.

15

3. The method as recited in claim 2, wherein the step b) includes:

b1) if the core network coupled is the asynchronous core network, setting the core network operating type information in the system information message as "0";

b2) if the core network coupled is the synchronous core network, setting the core network operating type information as "1"; and

b3) if both of the asynchronous core network and the synchronous core network are coupled to the mobile communication system, setting the core network operating type information as "0 & 1".

4. The method as recited in claim 1, wherein the step c) includes the steps of:

c1) receiving the system information message;

5 c2) extracting the core network operating type information from the system information message;

5. The method as recited in claim 4, wherein the step e) includes the steps of:

10 e1) if the core network operating type information represents that two core networks are coupled thereto, extracting the information related to the core network from the system information message;

15 e2) comparing the information related to the core network with information stored in the mobile station and corresponding to the information related to the core network; and

e3) selecting one core network to be coupled thereto based on a comparison result.

20 6. The method as recited in claim 3, wherein the core network operating type information and the information related to the core network are inserted into a master information block of the system information block.

25 7. The method as recited in claim 5, wherein the system information message is transmitted to the mobile station

through a broadcast channel (BCCH).

8. The method as recited in claim 1, wherein, if the selected core network is of the synchronous operating type,
5 the message includes new information elements related to the synchronous core network.

9. The method as recited in claim 5, wherein, if the core network coupled to the asynchronous mobile communication
10 system is of the asynchronous operating type, the information related to the core network includes a public land mobile network (PLMN) identity.

10. The method as recited in claim 5, wherein, if the
15 core network coupled to the asynchronous mobile communication system is of the synchronous operating type, the information related to the core network includes a protocol revision (P_REV), a minimum protocol revision (MIN_P_REV), a network identity (NID) and a system identity (SID).

20 11. The method as recited in claim 5, wherein, if the core network coupled to the asynchronous mobile communication system is of the synchronous operating type, the information related to the core network includes a public land mobile
25 network (PLMN) identity, a protocol revision (P_REV), a minimum protocol revision (MIN_P_REV), a network identity (NID) and a system identity (SID).

12. The method as recited in claim 11, wherein the step e2) includes the steps of:

e21) if the extracted PLMN identity is equal to a PLMN identity of the mobile station and the extracted MIN_P_REV is larger than a mobile protocol revision (MOB_P_REV) of the mobile station, selecting the asynchronous core network;

e22) if the extracted PLMN identity is not equal to the PLMN identity of the mobile station and the extracted MIN_P_REV is equal to or smaller than the MOB_P_REV of the mobile station, selecting the synchronous core network; and

e23) if the extracted PLMN identity is equal to the PLMN identity of the mobile station and the extracted MIN_P_REV is equal to or smaller than the MOB_P_REV of the mobile station, selecting the synchronous core network by using a core network selection method.

13. The method as recited in claim 12, wherein, if the core network is neither the asynchronous core network nor the synchronous core network, going back to step c1).

14. The method as recited in claim 12, wherein in the core network selection method, one core network is selected based on a number of transmission channels, a kind of systems and a kind of service provided by the mobile station, a transmission power of the mobile station and a frequency band occupied by the mobile station.

15. A method for transmitting a message between an asynchronous mobile communication system and at least a core network, the mobile communication system having a mobile station and a radio network, the method comprising the steps of:

a) at the radio network, discriminating an operating type of a core network(s) coupled thereto;

b) generating and transmitting a system information message having core network operating type information and information related to the core network;

c) if one core network is coupled to the asynchronous mobile communication system, communicating messages between the mobile station and the radio network, the message having a different data format according to the operating type of the core network;

d) if two or more core networks are coupled to the asynchronous mobile communication system, receiving an operating type of a core network selected by the mobile and communicating messages between the mobile station and the radio network, the message having a different data format according to the operating type of the core network.

16. The method as recited in claim 15, wherein the step a) includes:

a1) receiving core network operating type information; and

a2) determining whether the core network connected to the

asynchronous mobile communication system is a synchronous core network, asynchronous core network or both of the synchronous and the asynchronous core networks, based on the operating type of the core network.

5

17. The method as recited in claim 16, wherein the step b) includes:

b1) if the core network coupled is the asynchronous core network, setting the core network operating type information in the system information message as "0";

b2) if the core network coupled is the synchronous core network, setting the core network operating type information as "1"; and

b3) if both of the asynchronous core network and the synchronous core network are coupled to the mobile communication system, setting the core network operating type information as "0 & 1".

18. A method for transmitting a message between an asynchronous mobile communication system and at least a core network, the mobile communication system having a mobile station and a radio network, the method comprising the steps of:

a) at the mobile station, discriminating the operating type of the core network(s) based on a system information message received from the radio network;

b) if one core network is coupled to the asynchronous

mobile communication system, operating a call control entity and a mobility management entity according to the operating type of the core network;

c) if two or more core networks are coupled to the asynchronous mobile communication system, at the mobile station, selecting one core network to be communicated with, based on the system information message;

d) operating a call control entity and a mobility management entity according to an operating type of the selected core network;

e) informing the radio network of information related to the selected core network; and

f) communicating messages between the mobile station and the radio network, the message having a different data format according to the operating type of the core network.

19. The method as recited in claim 18, wherein the step a) includes the steps of:

a1) receiving the system information message;
a2) extracting the core network operating type information from the system information message;

20. The method as recited in claim 19, wherein the step c) includes the steps of:

c1) if the core network operating type information represents that two core networks are coupled thereto, extracting the information related to the core network from

the system information message;

c2) comparing the information related to the core network with information stored in the mobile station and corresponding to the information related to the core network;

5 and

c3) selecting one core network to be coupled thereto based on a comparison result.

21. The method as recited in claim 19, wherein the core network operating type information and the information related to the core network are inserted into a master information block of the system information block.

22. The method as recited in claim 21, wherein the system information message is transmitted to the mobile station through a broadcast channel (BCCH).

23. The method as recited in claim 18, wherein, if the selected core network is of the synchronous operating type, the message includes new information elements related to the synchronous core network.

24. The method as recited in claim 20, wherein, if the core network coupled to the asynchronous mobile communication system is of the asynchronous operating type, the information related to the core network includes a public land mobile network (PLMN) identity.

25. The method as recited in claim 20, wherein, if the core network coupled to the asynchronous mobile communication system is of the synchronous operating type, the information related to the core network includes a protocol revision (P_REV), a minimum protocol revision (MIN_P_REV), a network identity (NID) and a system identity (SID).

26. The method as recited in claim 20, wherein, if the core network coupled to the asynchronous mobile communication system is of the synchronous operating type, the information related to the core network includes a public land mobile network (PLMN) identity, a protocol revision (P_REV), a minimum protocol revision (MIN_P_REV), a network identity (NID) and a system identity (SID).

27. The method as recited in claim 21, wherein the step e2) includes the steps of:

e21) if the extracted PLMN identity is equal to a PLMN identity of the mobile station and the extracted MIN_P_REV is larger than a mobile protocol revision (MOB_P_REV) of the mobile station, selecting the asynchronous core network;

e22) if the extracted PLMN identity is not equal to the PLMN identity of the mobile station and the extracted MIN_P_REV is equal to or smaller than the MOB_P_REV of the mobile station, selecting the synchronous core network; and

e23) if the extracted PLMN identity is equal to the PLMN identity of the mobile station and the extracted MIN_P_REV is

equal to or smaller than the MOB_P_REV of the mobile station, selecting the synchronous core network by using a core network selection method.

5 28. The method as recited in claim 27, wherein, if the
core network is neither the asynchronous core network nor the
synchronous core network, going back to step c1).

29. The method as recited in claim 27, wherein in the
10 core network selection method, one core network is selected
based on a number of transmission channels, a kind of systems
and a kind of service provided by the mobile station, a
transmission power of the mobile station and a frequency band
occupied by the mobile station.

Abstract of the Disclosure

A method for The method for transmitting a message between a mobile communication system and at least a core network, the mobile communication system having a mobile station and a radio network, the method comprising the steps of: a) at the radio network, discriminating an operating type of a core network(s) coupled thereto; b) at the radio network, generating and transmitting a system information message having core network operating type information and information related to the core network; c) if two or more core networks are coupled to the asynchronous mobile communication system, at the mobile station, selecting one core network to be communicated with, based on the system information message; d) operating a call control entity and a mobility management entity according to an operating type of the selected core network; and e) communicating messages between the mobile station and the radio network, the message having a different data format according to the operating type of the selected core network.

FIG. 1A
(PRIOR ART)




FIG. 1B
(PRIOR ART)




FIG. 2A
(PRIOR ART)




FIG. 2B
(PRIOR ART)




FIG. 3A




FIG. 3B




FIG. 3C




FIG. 3D




FIG. 4A




FIG. 4B




FIG. 4C




FIG. 4D




FIG. 5




FIG. 6

INFORMATION ELEMENT	PRESENCE	RANGE	IE TYPE AND REFERENCE	SEMANTICS DESCRIPTION
OTHER INFORMATION ELEMENTS				
VALUE TAG	M			
REFERENCES TO OTHER SYSTEM INFORMATION BLOCKS		1.. <maxSysinfo Blockcount>		
SCHEDULING INFORMATION	M			
CN INFORMATION ELEMENTS				
CN TYPE	M		Enumerated (GSM-MAP, ANSI-41, GSM-MAP AND ANSI-41)	
PLMN_ID	C-GSM			
ANSI-41 INFORMATION ELEMENT	C-ANSI			
P_REV	M			
MIN_P_REV	M			
SID	M			
NID	M			

FIG. 7A




FIG. 7B




FIG. 8A




FIG. 8B




FIG. 9A






FIG. 9B





COMBINED DECLARATION AND POWER OF ATTORNEY

(Original, Design, National Stage of PCT, Divisional, Continuation or C-I-P Application)

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name; I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

METHOD FOR INTERFACING ASYNCHRONOUS MOBILE COMMUNICATION
SYSTEM WITH AT LEAST ONE CORE NETWORK

This declaration is of the following type:

- ☒ original
☐ design
☐ national stage of PCT
☐ divisional
☐ continuation
☐ continuation-in-part (C-I-P)

the specification of which: (complete (a), (b), or (c))

- (a) ☒ is attached hereto.
(b) ☐ was filed on _____ as Application Serial No. _____ and was amended
on _____ (if applicable).
(c) ☐ was described and claimed in PCT International Application No. _____ filed on
_____ and was amended on _____ (if applicable).

Acknowledgement of Review of Papers and Duty of Candor

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to the patentability of the subject matter claimed in this application in accordance with Title 37, Code of Federal Regulation § 1.56.

☐ In compliance with this duty there is attached an information disclosure statement. 37 CFR 1.98.

Priority Claim

I hereby claim foreign priority benefits under Title 35, United States Code, § 119(a)-(b) of any foreign application(s) for patent or inventor's certificate or of any PCT International Application(s) designating at least one country other than the United States of America listed below and have also identified below any foreign application(s) for patent or inventor's certificate or any PCT International Application(s) designating at least one country other than the United States of America filed by me on the same subject matter having a filing date before that of the application on which priority is claimed

(complete (d) or (e))

- (d) ☐ no such applications have been filed.
(e) ☒ such applications have been filed as follows:

PRIOR FOREIGN/PCT APPLICATION(S) FILED WITHIN 12 MONTHS(6 MONTHS FOR DESIGN) PRIOR TO SAID APPLICATION				
COUNTRY	APPLICATION NO.	DATE OF FILING (day, month, year)	DATA OF ISSUE (day, month, year)	PRIORITY CLAIMED UNDER 35 USC119
Republic of Korea	1999-46999	28/10/1999		[x] YES NO []
Republic of Korea	1999-51355	18/11/1999		[x] YES NO []
				[] YES NO []
ALL FOREIGN APPLICATION[S], IF ANY, FILED MORE THAN 12 MONTHS (6 MONTHS FOR DESIGN) PRIOR TO SAID APPLICATION				
				[] YES NO []
				[] YES NO []
				[] YES NO []

Claim for Benefit of Prior U.S. Provisional Application(s)

I hereby claim the benefit under Title 35, United States Code, § 119(e) of any United States provisional application(s) listed below:

Provisional Application Number	Filing Date

Claim for Benefit of Earlier U.S./PCT Application(s) under 35 U.S.C. 120

(complete this part only if this is a divisional, continuation or C-I-P application)

I hereby claim the benefit under Title 35, United States Code, § 120 of any United States application(s) or PCT international application(s) designating the United States of America that is/are listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior application(s) in the manner provided by the first paragraph of Title 35, United States Code § 112, I acknowledge the duty to disclose information as defined in Title 37, Code of Federal Regulations, § 1.56 which occurred between the filing date of the prior application(s) and the national or PCT international filing date of this application:

(Application Serial No.)	(Filing Date)	(Status(patented, pending, abandoned))
--------------------------	---------------	--

(Application Serial No.)	(Filing Date)	(Status(patented, pending, abandoned))
--------------------------	---------------	--

Power of Attorney

As a named inventor, I hereby appoint Dana M. Raymond, Reg. No. 18,540; Frederick C. Carver, Ref. No. 17,021; Francis J. Hone, Reg. No. 18,662; Joseph D. Garon, Reg. No. 20,420; Arthur S. Tenser, Reg. No. 18,839; Ronald B. Hildreth, Reg. No. 19,498; Thomas R. Nesbitt, Jr., Reg. No. 22, 075; Robert Neuner, Reg. No. 24,316; Richard G. Berkley, Reg. No. 25,465; Richard S. Clark, Reg. No. 26,154; Bradley B. Geist, Reg. No. 27,551; James J. Maune, Reg. No. 26,946; John D. Murnane, Reg. No. 29,836; Henry Tang, Reg. No. 29,705; Robert C. Scheinfeld, Reg. No. 31,300; John A. Fogarty, Jr., Reg. No. 22,348; Louis S. Sorell, Reg. No. 32,439; Rochelle K. Seide Reg. No. 32,300; Gary M. Butter, Reg. NO. 33,841; Marta E. Delsignore, Reg. No. 32,689; and Lisa B. Kole, Reg. No. 35,225 of the firm of BAKER BOTTS L.L.P., with offices at 30 Rockefeller Plaza, New York, New York 10112, as attorneys to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith

SEND CORRESPONDENCE TO:

BAKER BOTTS L.L.P.
30 ROCKEFELLER PLAZA, NEW YORK, N.Y. 10112
CUSTOMER NUMBER: 21003

DIRECT TELEPHONE CALLS TO:

BAKER BOTTS L.L.P.
(212)705-5000

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both,

under Section 1001 of Title 18 of the United States Code and that such willful false statement may jeopardize the validity of the application or any patent issued thereon.

FULL NAME OF SOLE OR FIRST INVENTOR	LAST NAME PARK	FIRST NAME JAE-HONG	MIDDLE NAME	
RESIDENCE & CITIZENSHIP	CITY Ichon-shi	STATE or FOREIGN COUNTRY Kyoungki-do, Korea	COUNTRY OF CITIZENSHIP Korea	
POST OFFICE ADDRESS	POST OFFCE ADDRESS San 136-1, Ami-ri, Bubal-eub	CITY Ichon-shi, Kyoungki-do	STATE or COUNTRY Korea	ZIP CODE 467-860
DATE 05/10/2000	SIGNATURE OF INVENTOR JAEHONG PARK			
FULL NAME OF SECOND JOINT INVENTOR, IF ANY	LAST NAME HWANG	FIRST NAME WOON-HEE	MIDDLE NAME	
RESIDENCE & CITIZENSHIP	CITY Ichon-shi	STATE or FOREIGN COUNTRY Kyoungki-do, Korea	COUNTRY OF CITIZENSHIP Korea	
POST OFFICE ADDRESS	POST OFFCE ADDRESS San 136-1, Ami-ri, Bubal-eub	CITY Ichon-shi, Kyoungki-do	STATE or COUNTRY Korea	ZIP CODE 467-860
DATE 25/08/2000	SIGNATURE OF INVENTOR WOONHEE HWANG			
FULL NAME OF THIRD JOINT INVENTOR, IF ANY	LAST NAME YE	FIRST NAME JEONG-HWA	MIDDLE NAME	
RESIDENCE & CITIZENSHIP	CITY Ichon-shi	STATE or FOREIGN COUNTRY Kyoungki-do, Korea	COUNTRY OF CITIZENSHIP Korea	
POST OFFICE ADDRESS	POST OFFCE ADDRESS San 136-1, Ami-ri, Bubal-eub	CITY Ichon-shi, Kyoungki-do	STATE or COUNTRY Korea	ZIP CODE 467-860
DATE 05/10/2000	SIGNATURE OF INVENTOR JEONG HWA YE			
FULL NAME OF FOURTH JOINT INVENTOR, IF ANY	LAST NAME	FIRST NAME	MIDDLE NAME	
RESIDENCE & CITIZENSHIP	CITY	STATE or FOREIGN COUNTRY	COUNTRY OF CITIZENSHIP	
POST OFFICE ADDRESS	POST OFFCE ADDRESS	CITY	STATE or COUNTRY	ZIP CODE
DATE	SIGNATURE OF INVENTOR			
FULL NAME OF FIFTH JOINT INVENTOR, IF ANY	LAST NAME	FIRST NAME	MIDDLE NAME	
RESIDENCE & CITIZENSHIP	CITY	STATE or FOREIGN COUNTRY	COUNTRY OF CITIZENSHIP	
POST OFFICE ADDRESS	POST OFFCE ADDRESS	CITY	STATE or COUNTRY	ZIP CODE
DATE	SIGNATURE OF INVENTOR			
FULL NAME OF SIXTH JOINT INVENTOR, IF ANY	LAST NAME	FIRST NAME	MIDDLE NAME	
RESIDENCE & CITIZENSHIP	CITY	STATE or FOREIGN COUNTRY	COUNTRY OF CITIZENSHIP	
POST OFFICE ADDRESS	POST OFFCE ADDRESS	CITY	STATE or COUNTRY	ZIP CODE
DATE	SIGNATURE OF INVENTOR			
FULL NAME OF SEVENTH JOINT INVENTOR, IF ANY	LAST NAME	FIRST NAME	MIDDLE NAME	
RESIDENCE & CITIZENSHIP	CITY	STATE or FOREIGN COUNTRY	COUNTRY OF CITIZENSHIP	
POST OFFICE ADDRESS	POST OFFCE ADDRESS	CITY	STATE or COUNTRY	ZIP CODE
DATE	SIGNATURE OF INVENTOR			

Check proper box(es) for any added page(s) forming a part of this declaration

[] Signature for ninth and subsequent joint inventors. Number of pages added _____.

- [illegible]